



AR 413 720

Metal housing
Inside installation
Air recirculation

Installation accessories

AA 010 410

Air exhaust grill recirculation mode
Stainless steel colored, 36",
including installation fittings,
height adjustable.

Optional accessories

Part# 703928

Activated charcoal filter for AR 413,
set of 4.

200 series recirculation blower

AR 413

- Easy and compact installation of 200 series VL 041/040 downdraft without exhaust ducts. Perfect for cooking islands
- To be combined with one or two downdrafts

Output

448 CFM unobstructed air flow.
Noise level depends on the
built-in situation.

Features

Metal housing, zinc-plated.
Duct connections air intake:
(2) \varnothing 6" round.
Spare cover for closing air intake.

Planning notes

Installation in the drawer area with
double height or on the floor with
cut-out in the furniture base. Air
intake with duct max. (2) \varnothing 8" behind
the drawers requires countertop
depth of min. 27". Cabinets without
toe-kick possible.
Up to two Vario 200 VL downdraft
units can be used with the AR 413
recirculation blower.

Please note: A second blower cannot
be independently controlled if used
with Vario 200 VL downdraft.

Rating

Total rating: 150 W.
Total Amps: 2 A.
120 V / 60 Hz
Plan for a 59 $\frac{1}{16}$ " connecting cable
without plug.

