



Version	Remote blower	Inline blower	Recirculation blower
Stainless steel	AR 401 740		
Metal zinc plated		AR 400 740	AR 413 720
Air extraction / recirculation	•/-	•/-	-/•
<b>Installation possibility</b>			
Roof	AA 401 920 <sup>1</sup>		
Outside wall	•		
Inside wall		•	•
Bottom cupboard		•	•
Attic		•	•
Cellar		•	•
<b>Dimensions</b>			
Width	(in inches) 14 7/16"	20 1/8"	23 5/8"
Depth	(in inches) 10 1/8"	16 3/4"	18 7/8"
Height	(in inches) 18 1/8"	10 1/16"	10 1/16"
Net weight	(in lbs.) 33	33	42
<b>Air extraction performance with unobstructed airflow, maximum</b>			
	ø 8	ø 8	
Air extraction	(CFM) 665	810	
Recirculation	(CFM)		448
<b>Features</b>			
Exhaust air intake connection piece, intake discharge ends	(ø in inches) 8"	8/4 x 6"	2 x 6"
Exhaust air outlet connection piece	(ø in inches) –	8"	
Number of fans	1	1	1
Motor output	(W) 520	520	150
Connecting cable length	(in inches) 39"	39"	39"
Additional connector pair for extension	•	•	
<b>Rating</b>			
Total rating	(W) 520	520	150
Total Amps	6	6	2
Electrical	120V/60Hz	120V/60Hz	120V/60Hz

• Included. – Not available.

<sup>1</sup> Optional accessory.