



## VI 263 620

Black control panel  
Width 24" (60 cm)

## Included accessories

1 glass scraper

## Installation accessories

### VV 200 010

Stainless steel connection strip for combination with other Vario 200 series appliances

### VV 200 020

Black connection strip for combination with other Vario 200 series appliances

## Optional accessories

### GP 900 001

Stainless steel frying sensor pan  
Non-stick coating, ø 6".

### GP 900 002

Stainless steel frying sensor pan  
Non-stick coating, ø 7".

### GP 900 003

Stainless steel frying sensor pan  
Non-stick coating, ø 8".

### GP 900 004

Stainless steel frying sensor pan  
Non-stick coating, ø 11".

## Combinable with:

VL200120  
AI442720 / AI442760  
AW442720 / AW442760  
AI230700  
AW230790  
AF210791 / AF210761

## Good to know:

Wall installations require the hood to be as large as the cooktop(s). Island installations require the hood to be larger than the cooktop(s).

## Vario 200 series induction cooktop VI 263

- Can be combined with other Vario 200 series products
- Control panel for comfortable and secure operation

## Cooking zones

3 cooking zones:

- 1 induction cooking zone 11" (2,600 W, with booster 3,700 W)
- 1 induction cooking zone 7" (1,800 W, with booster 3,100 W)
- 1 induction cooking zone 6" (1,400 W, with booster 2,200 W)

## Operation

Control knobs with illuminated ring.  
Integrated control panel.  
Electronic power control in 9 output levels.

## Features

Cooking area marking.  
Frying sensor function.  
Pot detection.  
Booster function for each cooking zone.

## Safety

Residual heat indication.  
Operation indicator.  
Safety shut-off.

## Planning notes

Operates with magnetic (induction) iron pots and pans only. For an optimal heat distribution, the use of flat bottom cookware is recommended.  
To insure that the appliance works correctly, the cooktop must be sufficiently ventilated either from the rear or base of the cabinet.  
Appliance can be snapped into the countertop from above.  
Appliance weight: approx. 30.8 lbs (14 kg).

## Rating

Rating: 7,400 W  
Minimum fuse protection: 30 A  
Electrical: 208 / 220–240 V / 60 Hz  
Electrical connection:  
Hardwire required, 37" cable length.

