



## Vario 200 series electric grill VR 230

**VR 230 620**  
Black aluminum control panel.  
Width 12" (28 cm).

### Included accessories

- 1 grease collecting insert.
- 1 cast iron grill.
- 1 lava stone.
- 1 cleaning brush.

### Installation accessories

#### VV 200 010

Stainless steel connection strip for combination with other Vario appliances of the 200 series.

#### VV 200 020

Black connection strip for combination with other Vario appliances of the 200 series.

### Optional accessories

#### LV 030 000

Lava stones for refilling.

#### VD 200 020

Black appliance cover.

### Combinable with:

- 2x VL 200 120
- AW 442 720
- AI 230 700
- AW 230 790
- AF 210 791

### Good to know:

Wall installations require the hood to be as large as the cooktop(s). Island installations require the hood to be larger than the cooktop(s).

### Highlights

- Can be combined with other Vario 200 series products.
- Control panel for comfortable and secure operation.
- 2 zones, separately controlled.
- Open cast iron grill, lava stones.
- Not recommended for recirculating ventilation.

### Operation

Control knobs with illuminated ring. Integrated control panel. 9 switching levels.

### Features

2 separately controllable swing-out grilling elements (1500 W). Join function. Cast iron grill. Stainless steel lavas tone container and grease collecting insert, dishwasher-safe.

### Safety

Pre-heat and residual heat indicator. Operation indicator. Safety shut-off.

### Planning notes

If using the VL 200 downdraft for ventilation, the Vario electric grill must be placed between two VL downdrafts. Recirculation is not recommended for the electric grill. Appliance can be snapped into the countertop from above. A minimum clearance of at least 8" (200 mm) from adjacent heat-sensitive cabinet or contact surfaces must be observed or thermal insulation fitted. Appliance weight: approx. 37.5 lbs (17 kg).

**Please read additional planning notes on page 117.**

### Rating

Rating: 3,000 W.  
Minimum fuse protection: 16 A.  
Electrical: 208 / 220-240 V / 60 Hz.  
Electrical connection:  
Hardwire required, 59" cable length.

