

Additional planning notes for dishwashers with flexible hinge – DF 480 / 481 (F)

For cut-out heights from 32 ³/₃₂" to 33 ²⁷/₃₂", in most cases, the Euro Tub dishwasher must be planned, regardless of the toe kick height.

For cut-out heights from 34 ²¹/₃₂" to 36 ¹⁹/₃₂", in most cases, the Tall Tub dishwasher must be planned, regardless of the toe kick height.

If the cut-out height amounts between 34 ¹/₁₆" and 34 ⁷/₁₆", please note: Whether the Euro Tub dishwasher or the Tall Tub dishwasher can be used here depends on the toe kick height.

If the installation of a dishwasher with **flexible hinge** is necessary or not depends on several factors.

The door panels cannot be used with dishwashers with flexible hinge.

Cabinet height 25 ¹³ / ₁₆ "–29 ¹ / ₂ " (655–755)										
Toe kick height in inches (mm)	Cut-out height in inches (mm) →									
	32 ³ / ₃₂ (815)	32 ⁹ / ₃₂ (820)	32 ¹⁵ / ₃₂ (825)	32 ¹¹ / ₁₆ (830)	32 ⁷ / ₈ (835)	33 ¹ / ₁₆ (840)	33 ⁹ / ₃₂ (845)	33 ¹⁵ / ₃₂ (850)	33 ²¹ / ₃₂ (855)	33 ²⁷ / ₃₂ (860)
2 (50) E										
2 ¹ / ₁₆ (55) E		E								
2 ¹ / ₈ (60) E		E	E							
2 ¹ / ₈ (65) E		E	E	E						
2 ¹ / ₄ (70) E		E	E	E	E					
3 (75) E		E	E	E	E	E				
3 ¹ / ₈ (80) E		E	E	E	E	E	E			
3 ¹ / ₈ (85) E		E	E	E	E	E	E	E		
3 ¹ / ₈ (90) E*		E	E	E	E	E	E	E	E	
3 ¹ / ₄ (95) E*		E*	E	E	E	E	E	E	E	E
4 (100) E*		E*	E*	E	E	E	E	E	E	E
4 ¹ / ₈ (105) E*		E*	E*	E*	E	E	E	E	E	E
4 ¹ / ₈ (110) E*		E*	E*	E*	E*	E	E	E	E	E
4 ¹ / ₂ (115) E*		E*	E*	E*	E*	E*	E	E	E	E
4 ³ / ₄ (120) E*		E*	E*	E*	E*	E*	E*	E	E	E
5 (125) E*		E*	E*	E*	E*	E*	E*	E*	E	E
5 ¹ / ₈ (130) E*		E*	E*	E*	E*	E*	E*	E*	E*	E
5 ¹ / ₈ (135) E*		E*	E*	E*	E*	E*	E*	E*	E*	E*
5 ¹ / ₂ (140) E*		E*	E*	E*	E*	E*	E*	E*	E*	E*
5 ¹¹ / ₁₆ (145) E*		E*	E*	E*	E*	E*	E*	E*	E*	E*
5 ³ / ₈ (150) E*		E*	E*	E*	E*	E*	E*	E*	E*	E*
6 ¹ / ₈ (155) E*		E*	E*	E*	E*	E*	E*	E*	E*	E*
6 ¹ / ₈ (160) E*		E*	E*	E*	E*	E*	E*	E*	E*	E*
6 ¹ / ₂ (165)		E*	E*	E*	E*	E*	E*	E*	E*	E*
6 ¹¹ / ₁₆ (170)			E*	E*	E*	E*	E*	E*	E*	E*
6 ³ / ₈ (175)				E*	E*	E*	E*	E*	E*	E*
7 (180)					E*	E*	E*	E*	E*	E*
7 ¹ / ₄ (185)						E*	E*	E*	E*	E*
7 ¹ / ₂ (190)							E*	E*	E*	E*
7 ¹¹ / ₁₆ (195)								E*	E*	E*
7 ³ / ₈ (200)									E*	E*
8 ¹ / ₁₆ (205)										E*
8 (210)										
8 ¹ / ₄ (215)										
8 ⁷ / ₁₆ (220)										

E = Euro Tub dishwasher with flexible hinge DF 480 763F, 32 ¹/₁₆" (81.5 cm) high

T = Tall Tub dishwasher with flexible hinge DF 481 763F, 32 ¹/₁₆" (86.5 cm) high

* Also possible with dishwashers without flexible hinge.

Additional planning notes – elevated installation of dishwashers with flexible hinge – DF 480 / 481 (F)

Elevated installation of dishwashers
with flexible hinge – **without slanted
drawer panel**

The table contains the gap size required between the kitchen cabinet door panel and drawer panel with reference to cut-out height, toe kick height and panel thickness when using a standard kitchen cabinet door panel for dishwashers installed below countertops.

Cut-out height inches (mm)	Panel thickness inches (mm)	Toe kick height inches (mm)								
		2 (50)	2 3/16 (55)	2 3/8 (60)	2 9/16 (65)	2 11/16 (70)	3 (75)	3 3/16 (80)	3 3/8 (85)	3 9/16 (90)
32 3/16 (815)	5/8 (16)	1/8 (3)	1/8 (3)	1/8 (3)	1/8 (3)	1/8 (3)	1/8 (3)	1/8 (3)	1/8 (3)	1/8 (3)
	3/4 (19)	1/8 (3)	1/8 (3)	9/64 (3.5)	9/64 (3.5)	9/64 (3.5)	9/64 (3.5)	9/64 (3.5)	9/64 (3.5)	9/64 (3.5)
	7/8 (22)	9/64 (3.5)	9/64 (3.5)	9/64 (3.5)	5/32 (4)	5/32 (4)	5/32 (4)	5/32 (4)	5/32 (4)	11/64 (4.5)
32 5/16 (820)	5/8 (16)		1/8 (3)	1/8 (3)	1/8 (3)	1/8 (3)	1/8 (3)	1/8 (3)	1/8 (3)	1/8 (3)
	3/4 (19)		1/8 (3)	1/8 (3)	9/64 (3.5)	9/64 (3.5)	9/64 (3.5)	9/64 (3.5)	9/64 (3.5)	9/64 (3.5)
	7/8 (22)		9/64 (3.5)	9/64 (3.5)	9/64 (3.5)	5/32 (4)	5/32 (4)	5/32 (4)	5/32 (4)	5/32 (4)
32 1/2 (825)	5/8 (16)			1/8 (3)	1/8 (3)	1/8 (3)	1/8 (3)	1/8 (3)	1/8 (3)	1/8 (3)
	3/4 (19)			1/8 (3)	1/8 (3)	9/64 (3.5)	9/64 (3.5)	9/64 (3.5)	9/64 (3.5)	9/64 (3.5)
	7/8 (22)			9/64 (3.5)	9/64 (3.5)	9/64 (3.5)	5/32 (4)	5/32 (4)	5/32 (4)	5/32 (4)
32 11/16 (830)	5/8 (16)				1/8 (3)	1/8 (3)	1/8 (3)	1/8 (3)	1/8 (3)	1/8 (3)
	3/4 (19)				1/8 (3)	1/8 (3)	9/64 (3.5)	9/64 (3.5)	9/64 (3.5)	9/64 (3.5)
	7/8 (22)				9/64 (3.5)	9/64 (3.5)	9/64 (3.5)	5/32 (4)	5/32 (4)	5/32 (4)
32 7/8 (835)	5/8 (16)					1/8 (3)	1/8 (3)	1/8 (3)	1/8 (3)	1/8 (3)
	3/4 (19)					1/8 (3)	1/8 (3)	9/64 (3.5)	9/64 (3.5)	9/64 (3.5)
	7/8 (22)					9/64 (3.5)	9/64 (3.5)	9/64 (3.5)	5/32 (4)	5/32 (4)
33 1/8 (840)	5/8 (16)						1/8 (3)	1/8 (3)	1/8 (3)	1/8 (3)
	3/4 (19)						1/8 (3)	1/8 (3)	9/64 (3.5)	9/64 (3.5)
	7/8 (22)						9/64 (3.5)	9/64 (3.5)	9/64 (3.5)	5/32 (4)
33 9/16 (845)	5/8 (16)							1/8 (3)	1/8 (3)	1/8 (3)
	3/4 (19)							1/8 (3)	1/8 (3)	9/64 (3.5)
	7/8 (22)							9/64 (3.5)	9/64 (3.5)	9/64 (3.5)
33 1/2 (850)	5/8 (16)								1/8 (3)	1/8 (3)
	3/4 (19)								1/8 (3)	1/8 (3)
	7/8 (22)								9/64 (3.5)	9/64 (3.5)
33 11/16 (855)	5/8 (16)									1/8 (3)
	3/4 (19)									1/8 (3)
	7/8 (22)									9/64 (3.5)
33 7/8 (860)	5/8 (16)									
	3/4 (19)									
	7/8 (22)									
34 1/8 (865)	5/8 (16)		1/8 (3)	1/8 (3)	1/8 (3)	1/8 (3)	1/8 (3)	1/8 (3)	1/8 (3)	1/8 (3)
	3/4 (19)		1/8 (3)	1/8 (3)	9/64 (3.5)	9/64 (3.5)	9/64 (3.5)	9/64 (3.5)	9/64 (3.5)	9/64 (3.5)
	7/8 (22)		9/64 (3.5)	9/64 (3.5)	9/64 (3.5)	5/32 (4)	5/32 (4)	5/32 (4)	5/32 (4)	11/64 (4.5)
34 1/4 (870)	5/8 (16)			1/8 (3)	1/8 (3)	1/8 (3)	1/8 (3)	1/8 (3)	1/8 (3)	1/8 (3)
	3/4 (19)			1/8 (3)	1/8 (3)	9/64 (3.5)	9/64 (3.5)	9/64 (3.5)	9/64 (3.5)	9/64 (3.5)
	7/8 (22)			9/64 (3.5)	9/64 (3.5)	9/64 (3.5)	5/32 (4)	5/32 (4)	5/32 (4)	5/32 (4)
34 1/2 (875)	5/8 (16)			1/8 (3)	1/8 (3)	1/8 (3)	1/8 (3)	1/8 (3)	1/8 (3)	1/8 (3)
	3/4 (19)			1/8 (3)	1/8 (3)	9/64 (3.5)	9/64 (3.5)	9/64 (3.5)	9/64 (3.5)	9/64 (3.5)
	7/8 (22)			9/64 (3.5)	9/64 (3.5)	9/64 (3.5)	5/32 (4)	5/32 (4)	5/32 (4)	5/32 (4)
34 11/16 (880)	5/8 (16)				1/8 (3)	1/8 (3)	1/8 (3)	1/8 (3)	1/8 (3)	1/8 (3)
	3/4 (19)				1/8 (3)	1/8 (3)	9/64 (3.5)	9/64 (3.5)	9/64 (3.5)	9/64 (3.5)
	7/8 (22)				9/64 (3.5)	9/64 (3.5)	9/64 (3.5)	5/32 (4)	5/32 (4)	5/32 (4)
34 7/8 (885)	5/8 (16)					1/8 (3)	1/8 (3)	1/8 (3)	1/8 (3)	1/8 (3)
	3/4 (19)					1/8 (3)	1/8 (3)	9/64 (3.5)	9/64 (3.5)	9/64 (3.5)
	7/8 (22)					9/64 (3.5)	9/64 (3.5)	9/64 (3.5)	5/32 (4)	5/32 (4)
35 1/8 (890)	5/8 (16)						1/8 (3)	1/8 (3)	1/8 (3)	1/8 (3)
	3/4 (19)						1/8 (3)	1/8 (3)	9/64 (3.5)	9/64 (3.5)
	7/8 (22)						9/64 (3.5)	9/64 (3.5)	9/64 (3.5)	5/32 (4)
35 1/4 (895)	5/8 (16)							1/8 (3)	1/8 (3)	1/8 (3)
	3/4 (19)							1/8 (3)	1/8 (3)	9/64 (3.5)
	7/8 (22)							9/64 (3.5)	9/64 (3.5)	9/64 (3.5)
35 7/16 (900)	5/8 (16)								1/8 (3)	1/8 (3)
	3/4 (19)								1/8 (3)	1/8 (3)
	7/8 (22)								9/64 (3.5)	9/64 (3.5)
35 5/8 (905)	5/8 (16)									1/8 (3)
	3/4 (19)									1/8 (3)
	7/8 (22)									9/64 (3.5)
35 7/8 (910)	5/8 (16)									
	3/4 (19)									
	7/8 (22)									
36 1/16 (915)	5/8 (16)									
	3/4 (19)									
	7/8 (22)									
36 1/4 (920)	5/8 (16)									
	3/4 (19)									
	7/8 (22)									
36 7/16 (925)	5/8 (16)									
	3/4 (19)									
	7/8 (22)									

Additional planning notes – elevated installation of dishwashers with flexible hinge – DF 480 / 481 (F)

Elevated installation of dishwashers with flexible hinge – **with slanted drawer panel**

The table contains the gap size required between the kitchen cabinet door panel and drawer panel with reference to cut-out height, toe kick height and panel thickness when using a standard kitchen cabinet door panel for dishwashers installed below countertops.

[illegible]

