GAGGENAU

Combi-steam oven
Gaggenau Expressive series
GS 470/GS 471

Right-hinged

GS 470 720
Stainless steel behind smoked glass.
Plumbed. Water and drain line required.
Width 24″ (60 cm).

Left-hinged

GS 471 720
Stainless steel behind smoked glass.
Plumbed. Water and drain line required.
Width 24″ (60 cm).

Included accessories

1 cooking container, stainless steel, perforated.
1 cooking container, stainless steel, unperforated.
1 door opening aid.
1 wire rack.
1 water inlet hose 118″ (3 m).
1 water outlet hose 118″ (3 m).
4 cleaning cartridges.

Installation accessories

GA 601 010
Gaggenau adjustable shelf.
Installation kit for 24″ (60 cm) appliances. For use in vertical installations where a perfect 3/16″ (5 mm) gap between Gaggenau Expressive Series appliances, and a single cut out are desired. Can support
GS Combi-steam oven,
GM Combi-microwave oven, or
GC Fully automatic coffee machine.
Note this is not required as standard cabinet shelves can
be used.
Includes mounting brackets, cover and screws.
Please note the following two exceptions for the use of the Gaggenau adjustable shelf:
— Exception One: When stacking a GO oven on top of another GO oven, a standard cabinet shelf (wood) is required.
— Exception Two: When stacking a GC coffee machine above a GM Combi-microwave oven, a standard cabinet shelf (wood) is required.

GZ 010 011
Extension for water inlet and outlet 78″ long (2 m).

Required accessories

Part No. 00312528
Descaling tablets.

Optional accessories

BA 010 051
Core temperature probe.
Compatible with GO, GS, GM.

BA 010 301
Triple telescopic pull-out rack for Combi-steam ovens.

BA 020 361
Cooking container, stainless steel, unperforated, 1 13/16″ deep (46 mm), 4.8 qt. (5.4 l).

BA 020 370
Cooking container, stainless steel, perforated, 1 9/16″ deep (40 mm), 4.4 qt. (5 l).

BA 020 382
Cooking container, unperforated, PFAS free non-stick coating, 1 13/16″ deep (46 mm), 4.8 qt. (5.4 l).

BA 020 391
Insert, perforated, PFAS free non-stick coating, 1 9/16″ deep (40 mm), 4.4 qt. (5 l).

BA 046 118
Glass tray.
1″ deep (24 mm).

CLS 100 40
Cleaning cartridges, set of 4.
For Combi-steam ovens.

GN 010 330
Adapter for gastronorm insert and roaster.

GN 114 130
Gastronorm insert, stainless steel, GN 1/3.
Unperforated, 1 9/16″ deep (40 mm), 1.3 qt. (1.5 l).

GN 114 230
Gastronorm insert, stainless steel, GN 2/3.
Unperforated, 1 9/16″ deep (40 mm), 2.6 qt. (3 l).

GN 124 130
Gastronorm insert, stainless steel, GN 1/3.
Perforated, 1 9/16″ deep (40 mm), 1.3 qt. (1.5 l).

GN 124 230
Gastronorm insert, stainless steel, GN 2/3.
Perforated, 1 9/16″ deep (40 mm), 2.6 qt. (3 l).

GN 340 231
Gastronorm roaster in cast aluminum GN 2/3, height 6 1/2″ (165 mm), PFAS free non-stick coating.
In combination with adapter GN 010 330 and triple pull-out rail BA 010 301.

Part No. 10044742
Door opening aid door accessory.

Highlights

— Handleless full glass door with electronic door opening.
— Full touch display with stainless steel control ring.
— Light and display response upon user detection.
— Fixed inlet and outlet water connection for convenient operation.
— External steam generation to avoid limescale in the cooking compartment.
— Automatic cleaning with perfect results, also for heavy soiling.
— Convection 86 °F to 445 °F, freely combinable with humidity levels 0%, 30%, 60%, 80% or 100%.
— Sous-vide cooking with accurate temperature regulation.
— Full surface broiler behind glass ceramic, combinable with circulated air up to 445 °F and steam.
— Automatic programs and setting recommendations.
— Oven cavity size 2.1 cu. ft. (59 liters).
— Sabbath mode certified by Star-K.

Heating methods / Programs

Convection + 100 % humidity.
Convection + 80 % humidity.
Convection + 60 % humidity.
Convection + 30 % humidity.
Convection + 0 % humidity.
Broil + circulated air.
Broil level 1 + humidity.
Broil level 2 + humidity.
Sous vide.
Low temperature.
Dough proofing.
Keep warm.
Defrost.
Reheat.
200 programs
(automatic programs and setting recommendations).
Option to save up to 30 favorites.

Operation

Soft-close side-opening door with 110° opening angle.
Electronic door opening.
Full touch display with control ring.
42 display languages available.
User detection, adjustable distance.
Information key with use indicators.
Animated quick guides to assist appliance operation.

Features

Full surface broiler 2,000 W behind glass ceramic.
Convection fan rotates in both directions for ideal heat distribution.
Connection for core temperature probe (oven temperature probe usable).
Broil can be added briefly in convection mode for additional browning.
Misting for targeted humidity addition.
Steam removal to avoid humidity on cabinet fronts.
Automatic boiling point detection.
Precise temperature control with display of the current temperature.
Timer functions: cooking time, cooking time end, count-up timer.
Long-term timer (Sabbath mode, Star-K certified).
Programmable automatic door opening at cooking time end to avoid overcooking.
Optimum visibility of the food thanks to side lighting.
3 rack levels.

Selected digital services (Gaggenau Home Connect®)

Remote control and monitoring.
Cooking time estimation when using the core temperature probe.
Door opening via voice assistant.

Please read additional information on Gaggenau Home Connect® on page 271.

Safety

Child lock to prevent accidental switch on or operation of the appliance.
Electronic door lock to prevent unintentional opening of the appliance door.
Safety shut-off.
Thermally insulated door with triple glazing.
Cooled housing with temperature protection.

Cleaning

Hygienic stainless steel cooking interior.
Automatic cleaning.
Automatic descaling for the steam generator.
Drying program.
Automatic drying of the cavity at the end of the cooking process.
All removable parts and accessories dishwasher-safe, incl. stainer filter.

Planning notes

Plan the cut out without back wall.
Door hinge not reversible.
No other electrical appliances should be installed above the GS.
At no point may the outlet hose be positioned higher than the bottom edge of the appliance. The outlet hose must also be at least 4″ (100 mm) lower than the appliance outlet (see drawing “drainage connection”).
Inlet and outlet hose can be extended once.
The outlet hose must not be longer than a maximum of 196″ (5 m).
The water connection for the inlet hose must always be accessible and not located directly behind the appliance.
The connection of the outlet hose to the siphon must not be directly behind the appliance and should be accessible.
Protrusion from appliance front to cabinet 1 5/8″ (42 mm).
Consider the overhang when planning to open drawers next to the appliance.
When planning a corner solution, pay attention to the side-opening door and the minimum required distance to the wall.
Door opening angle appr. 110° (delivery status) can be reduced to appr. 97° if required.
The door opening aid accessory should be attached before Shabbos, as it may not be permanently attached on Shabbos.
The electrical box must be accessible and located outside the built-in cut out.

www.gaggenau.com/us
Revised: September 2026

Gaggenau reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product’s installation instructions for final dimensional data and other details prior to making cut out. Warranties: Please see Use & Care manual or Gaggenau website for statement of limited product warranty. For more information on our entire line of products, go to www.gaggenau.com or call 1-877-442-4436.

GAGGENAU

Rating
Total rating: 2,550 W (208 V); 3,450 W (240 V).
Total amps: 14.4 A.
Minimum fuse protection: 15 A, double-pole breaker.
120/208 – 240 V, 60 Hz, 3-wire.
Plan for a 63" connecting cable (hardwire required).
Gaggenau Home Connect® functionality via WiFi.
Cold water connection: ¾" inner diameter, 1" outer diameter.

To enable water detection, softened water must have a total dissolved solids (TDS) level greater than 100 ppm (parts per million).
Water inlet hose 118" (3.0 m) with connection pipe thread ISO228-G ¾" Ø (26.4 mm), extendable, is included.
Drain connection:
Water outlet hose 118" (3.0 m) (HT-Hose), 1" Ø (25 mm), extendable, is included. Drain size: 1" diameter minimum.
Vacuum break recommended.



A: Accessible electrical connection
B : Accessible water connection
C: Fixed cable
* The width tolerance as shown in the drawing indicated by the + 5/16" (+8 mm) is the adjustment possible within the cabinet. Adjustments can be made between 5/8" – 13/16" (16-20 mm) for installation using the "centering parts" within the cabinet for perfect alignment. See installation instructions for details.



Numbers indicated
inside parenthesis ( ) = mm

www.gaggenau.com/us
Revised: September 2026

PFAS

Gaggenau reserves the absolute and unrestricted right to change product materials and specifications, at any time, without notice. Consult the product's installation instructions for final dimensional data and other details prior to making cut out. Warranties: Please see Use & Care manual or Gaggenau website for statement of limited product warranty. For more information on our entire line of products, go to www.gaggenau.com or call 1-877-442-4436.