# Checklist for appliance combinations Gaggenau Expressive series

This checklist provides the most relevant parameters for the perfect combination and ordering of Ovens, Combi-steam ovens, Combi-microwave ovens, Fully automatic espresso machines, Vacuuming drawers and Warming drawers.

#### In general

- All appliances shown can be obtained with stainless steel-backed smoked glass front.
- It is recommended to increase the cabinet depth to ≥ 23 1/16" (585 mm) when several appliances are combined.

#### **Horizontal combinations**

When planning and ordering please note that


- The door hinges need to be placed on the outside.
- The door hinge (right-/left-hinged) is not reversible.
- The clearance between the appliances must be at least ¼" (6 mm).
- Combi-steam ovens (GS), Combi-microwave ovens (GM) and Fully automatic espresso machine (GC) in combination with a Vacuuming drawer (GV) or a Warming drawer (GW) (5 1/4" (14 cm) in height) have the same total front height as a 24" (60 cm) oven.


#### **Vertical combinations**

When planning and ordering please note that

- To optimize ergonomics, the hinges should be placed on the outside.
- The door hinge (right-/left-hinged) is not reversible.
- In a corner situation, the distance to the wall of the appliance with the widest opening must be taken into account (e.g. Espresso machine (GC)).
- The width of the appliances is identical.
- No other electrical appliances should be installed above the Combi-steam oven (GS).
- Installation of an Espresso machine (GC) above a Combi-microwave oven (GM) is only possible with a standard cabinet shelf. The use of the Gaggenau adjustable shelf GA 601 010 is not permitted in this case.
- Stacking two Ovens (GO) is only possible with a standard cabinet shelf. The use of the Gaggenau adjustable shelf GA 301 010/ GA 601 010 is not permitted in this case due to the oven's weight.
- Appliances installed above a dishwasher need a separate cut out.


### Horizontal 24" (60 cm)






Combination EH66\_14\_RNA (For dimensions, see page 7)

#### Horizontal 30" (76 cm)




Combination EH33\_21\_RNA (For dimensions, see page 7)

### Horizontal Mix 24" & 30" (60 cm & 76 cm)



Combination EH36\_21\_RNA (For dimensions, see page 8)



Combination EH363\_21\_RNA (For dimensions, see page 8)

www.gaggenau.com/us Revised: June 2025

GO Oven

GS Combi-steam oven

GM Combi-microwave oven

GC Fully automatic espresso machine


GV Vacuuming drawer

GW Warming drawer


### Vertical 24" (60 cm)



**Combination EV6\_0\_H45\_RNA** (For dimensions, see page 9)




Combination EV6\_14\_H45\_RNA (For dimensions, see page 9)




Combination EV6\_21\_H45\_RNA (For dimensions, see page 9)

### Vertical 30" (76 cm)




Combination EV3\_0\_H45\_RNA

(For dimensions, see page 10)



Combination EV3\_21\_H45\_RNA


(For dimensions, see page 10)



Combination EV3\_0\_RNA


(For dimensions, see page 10)

### Cube 24" (60 cm)



Combination ECU66\_14\_H45\_RNA (For dimensions, see page 11)

### Cube Mix 24" & 30" (60 cm & 76 cm)



 $\textbf{Combination ECU63\_21\_H45\_RNA} \ (\textbf{For dimensions}, \textbf{see page 11})$ 

# Planning notes for the installation of ovens and oven combinations Gaggenau Expressive series

#### General notes

#### Installation behind kitchen cabinet doors


Appliance to be operated only with open doors. Appropriate measures must be taken to prevent these types of doors from closing when the appliance is heating or while it is cooling down (fan in operation).

#### Installation side by side

When appliances are installed side by side, the clearance between the appliances must be at least ½" (6 mm) (corresponds to the standard outside measurement of the cabinet cut out of  $23 \, {}^5\!\!/\!\! e$ " (600 mm) or  $30 \, {}^m$  (762 mm)). To optimize ergonomics, the hinges should be placed on the outside.

# Combination of ovens and Vario cooling 400 series appliances

Please check the planning notes in the information for cooling appliances.



# Reduced gaps between appliances and cabinet fronts

Gaggenau ovens (GO) are cooled with fresh air at the top edge of the frame. Hot air is blown out at the frame bottom edge.

Combi-steam ovens (GS) and Combi-microwave ovens (GM) have the air inlet at the side edges of the frame and the hot air and steam outlets horizontally at the top edge of the frame.

Take into account the minimum needed gaps.

The measurements given in the drawing apply to all appliances.

The following must also be respected:

The area above the appliances **GS:** 

No other electrical appliances should be installed above the Combi-steam oven (GS).

Front edges of the cabinet panel must be steam resistant as is the case above a dishwasher. Steam may possibly penetrate into the compartment.

### GC:

Installation of an Espresso machine (GC) above a Combi-microwave oven (GM) is only possible with a standard cabinet shelf. The use of the Gaggenau adjustable shelf GA 601 010 is not permitted in this case.

### GM:

To comply with UL/CSA norm, the top upper edge of the Combi-microwave oven (GM) front must be at a minimum height of  $\geq$  31" (787 mm).




#### At the sides

Pay attention to the door opening angles and required distances which may be different depending on the appliances.

The default door opening angle is 110°.
This angle can be reduced by adjusting it on the appliance.

### Door opening angle and distances



A: All 24" (60 cm) appliances except Espresso machine (GC)
B: Espresso machine (GC) appliances (only left hinged)
To reduce angle 110° to 92° with a distance ≥ 3 15/16" (≥ 100 mm),
Part No. 10020570 is required.
C: All 24" (60 cm) appliances except Espresso machine (GC)




# Planning notes for the installation of ovens and oven combinations Gaggenau Expressive series

**Guidelines for Flush installation** 

Proper planning, measurement, and installation techniques are required to achieve a seamless flush integration. Ensure that the appliance's depth, including the frame, are taken into account. Ensure that the cabinetry is level and structurally sound to support the appliance's weight. If needed, use Gaggenau adjustable shelf GA 301 010/GA 601 010 as recommended to securely support Combi-steam oven (GS), Combi-microwave oven (GM), or Fully automatic espresso machine (GC) within the cabinet space. In cases where the appliance combination includes a Vacuuming drawer (GV) or a Warming drawer (GW), it is necessary to raise these appliances by  $\frac{3}{16}$ " (5 mm) to allow them to open properly. This  $\sqrt[3]{16}^{\prime\prime}$  (5 mm) rise must be taken into account for the cabinet height. In a horizontal combination that includes a Vacuuming drawer (GV) or a Warming drawer (GW), it is necessary to raise all appliances in the adjacent cut outs by 3/16" (5 mm)


for proper alignment. (e.g., oven).



A: An elevation of \$\frac{3}{16}" (5 mm) is required to ensure that GW/GV opens properly. If the GW/GV is not present, the elevation is unnecessary; however, please ensure that there is a gap of 2 1/8" (2 3 mm) to the front helow

B: Gagganau adjustable shelf GA 301 010/GA 601 010


Cabinet dimensions
Appliance dimensions



Shortened side panel
Wooden panel for elevation


# Combinations Gaggenau Expressive series


### Combination - Horizontal 24" (60 cm) - EH66\_14\_RNA



A: Cabinet front


### Combination — Horizontal 30" (76 cm) — EH33\_21\_RNA










### Combination — Horizontal Mix 24" & 30" (60 cm & 76 cm) — EH36\_21\_RNA






### Combination — Horizontal Mix 24" & 30" (60 cm & 76 cm) — EH363\_21\_RNA









A: Cabinet front

# Combinations Gaggenau Expressive series


### Combination - Vertical 24" (60 cm) - EV6\_0\_H45\_RNA



### Combination - Vertical 24" (60 cm) - EV6\_14\_H45\_RNA



### Combination - Vertical 24" (60 cm) - EV6\_21\_H45\_RNA




Position of Gaggenau adjustable shelf GA 601 010, GA 301 010

Position of Gaggenau adjustable shelf GA 601 010 with GC at top


Numbers indicated inside parenthesis ( ) = mm www.gaggenau.com/us Revised: June 2025

# Combinations Gaggenau Expressive series


### Combination - Vertical 30" (76 cm) - EV3\_0\_H45\_RNA



### Combination - Vertical 30" (76 cm) - EV3\_21\_H45\_RNA




## Combination — Vertical 30" (76 cm) — EV3\_0\_RNA



Numbers indicated inside parenthesis ( ) = mm

www.gaggenau.com/us Revised: June 2025


### Combination - Cube 24" (60 cm) - ECU66\_14\_H45\_RNA



**B:** Gaggenau adjustable shelf

C: Reference line

### Combination — Cube Mix 24" & 30" (60 cm & 76 cm) — ECU63\_21\_H45\_RNA



A: Cabinet front

**B:** Gaggenau adjustable shelf

C: Reference line

17<sup>15</sup>/16 (456)

23<sup>1</sup>/<sub>2</sub> (596) 41<sup>5</sup>/8 (1057)