



## Vario fridge-freezer combination Gaggenau Expressive series RVY 497

**RVY 497 790**  
Fully integrated, panel ready, with internal water dispenser. Cut out width 35 1/2" (90 cm). Cut out height 84" (213.4 cm). Cooling compartment with two doors and one fully extendable freezing drawer.

### Included accessories

- 1 egg holder with lid.
- 1 ice cube scoop.
- 1 ice storage container.
- 2 oak wood bottle supports.
- 1 supply hose, 70 7/8" (1.8 m) with 1/4" female compression fitting.
- 1 ethylene absorber starter kit.
- 1 activated charcoal water filter.

### Required accessories

**RVA 460 000**  
Required accessory for Expressive series side-by-side installation.

### Installation accessories

**RVA 421 922**  
Dark brushed stainless steel door panels with handles. For RVY 497, panel thickness 3/4" (19 mm).

**RVA 428 922**  
Dark brushed stainless steel door panels, handleless. For RVY 497, panel thickness 3/4" (19 mm).

**RA 421 915**  
Stainless steel door panels, with handles. For RY/RVY 497, panel thickness 3/4".

**RA 425 110**  
Handle bar, stainless steel, long. With 3 mounts, length 44 1/2" (1131 mm), height 1 15/16" (49 mm), drilling distance between each mount 21 13/16" (554 mm). Order quantity 2x required.

**RA 425 910**  
Handle bar, stainless steel, short. For RVY 497, RVB 497 and RW 222, with 2 mounts, length 31 1/8" (810 mm), height 1 15/16" (49 mm), drilling distance between the mounts 31" (787 mm).

**RVA 423 141**  
Side trims used to conceal the gap between the appliance and adjacent cabinet. 1/8" (3 mm), 2 pieces.



**RA 460 030**  
Connecting element for vertically split fronts (for fridge-freezer combination).

**RVA 460 900**  
Accessory for replacing side-by-side installation in unmodified cut out. Required if an RVY 497, RVB 497, RVC 497 or RVF 497 (35 3/16" (89.4 cm) wide) is installed side-by-side into a cut out which was formerly housing a combination including an RY 492, RB 492 or RC 492 (35 3/4" (90.8 cm) wide).

**RVA 460 910**  
Accessory for replacement in single unmodified cut out. Required if an RVY 497, RVB 497, RVC 497 or RVF 497 (35 3/16" (89.4 cm) is replacing an RY 492, RB 492 or RC 492 (35 3/4" (90.8 cm) wide).

**RVA 460 020**  
Accessory for side-by-side installation, backward compatible. Required if a Vario cooling Expressive series appliance is installed side-by-side with a Vario cooling 400 series appliance.

### Optional accessories

**RA 430 100**  
Storage container with transparent lid, anthracite.

**Part No. 11031964**  
Egg holder insert (for use with RA 430 100).

**RVA 438 040**  
Solid oak wood bottle support with magnetic connector.

**RA 450 022**  
Activated charcoal water filter. For RVY, RVB and RVF.

**Part No. 11049963**  
Water filter bypass for home water filtration system.

**RVA 450 220**  
Replacement activated charcoal air filter, set of 2 pcs.

**Part No. 17006999**  
Ethylene absorber. Starter kit. For placement in a fresh climate drawer.

**Part No. 17007000**  
Ethylene absorber. Refill kit. For placement in a fresh climate drawer.

### Highlights

- Dark brushed stainless steel interior, refined with solid anthracite aluminum elements.
- Warm white and glare-free LED lighting concept for optimal food presentation in all compartments.
- Opening assist for door with two options:
  1. Push-to-open function for integration into handleless cabinet front.
  2. Pull-to-open function to facilitate opening the door using a handle.
- Flat dark brushed stainless steel inner door.
- Flexible positioning of shelves and door racks through hidden rail system.
- Solid anthracite aluminum door racks.
- Professional freshness system with 2 fresh climate drawers and 1 chilled drawer.
- Internal water dispenser with water filter located on the left side above fresh climate drawers.
- Integrated ice maker with fixed water connection.
- Spacious, fully extendable freezer compartment including 2 additional interior drawers.
- Full touch TFT display.
- ENERGY STAR® certified.
- Sabbath mode certified by Star-K.
- Total volume: 20 cu.ft.

### Operation

Opening assist for door and drawer. Soft-close door closing system. User guidance through light and display response to drawer interaction. Automatic brightness adjustment based on ambient illumination. Easily accessible full touch TFT display. Clear text display. Animated quick guides to assist appliance maintenance.

### Technical features

Dynamic cold air distribution. Automatic defrosting with defrost water evaporation. Constant air purification by 2 activated charcoal air filters. Sabbath mode certified by Star-K. When sabbath mode is active, the appliance can only be opened using a handle. Open-door and malfunction alarm.

### Selected digital services (Gaggenau Home Connect)

Remote control and monitoring. Storage management with cameras. Automatic program selection of fresh climate drawers (via object recognition). Personalization function for saving custom programs.

### Cooling

Internal water dispenser with water filter. Professional freshness system. No-frost technology with fast cooling. Temperature adjustable from 35 °F to 46 °F (+2 °C to +8 °C). 3 aluminum-framed safety glass shelves, individually adjustable in height. 1 integrated safety glass shelf. Optimal food presentation with warm white and glare-free, hidden LED light bars (3000 K). Flexible positioning of door racks through hidden rail system.

6 door racks, of that 4 are height adjustable. Total volume of all refrigerator compartments: 13.2 cu.ft.

### Fresh climate drawer

2 fresh climate drawers with humidity control. Temperature adjustable from 30 °F to 36 °F (-1 °C to +2 °C). Ideal storage conditions for different foods through dedicated programs (e.g. Fruit, Vegetables, Meat). Individual adjustment of temperature and humidity. Extended food preservation with ethylene absorber. Indirect illumination, transparent front. Fully extendable, with soft-close drawer closing system.

### Chilled drawer

Temperature is always 3.5 °F to 5.5 °F (2 °C to 3 °C) lower than the cooling compartment. Indirect illumination, transparent front. Fully extendable, with soft-close drawer closing system.

### Freezing

No-frost technology with fast freezing at -22° F (-30° C). 4-star freezer compartment. Temperature adjustable from -11 °F to 3 °F (-24 °C to -16 °C). Freezer burn protection. Oxidation protection. Spacious, fully extendable freezer compartment with synchronously running pull-out rails. 2 extendable interior drawers. Warm-white, glare-free LED lighting (3000 K) within freezer compartment. Net volume 6.8 cu.ft.

### Ice maker

Integrated automatic ice maker in the freezer compartment, with fixed water connection. Ice maker can be switched off independently. Ice cube production approx. 5.5 lbs. (2.5 kg)/24 h. Removable ice storage container with approx. 7 lbs. (3.2 kg) capacity. Integrated, easily accessible ice cube scoop. Active charcoal water filter for water inlet, integrated in ventilation grill area. Saturation indicator for filter via full touch TFT display.

### Consumption data

Energy consumption 597 kWh/year. Noise level 39 dB (A) re 1 pW.

### Planning notes

Flat hinge. Door opening angle of 115°, fixable at 90°. Max. door panel weight: Each door 141 lbs. (64 kg). Drawer 30 lbs. (14 kg). Shut-off valve for water connection must be planned next to the appliance and always be accessible. If the water pressure exceeds 116 psi (8 bar), connect pressure relief valve between water tap and hose set. Standard brushed stainless steel door panels with handles (not dark brushed stainless steel) are available to order, but require a larger 36" (914 mm) wide cut out in order to accommodate the larger doors. Please order RA 421 915 (standard stainless steel doors) and RVA 460 910 (installation accessory). Consult planning notes for additional detail.

www.gaggenau.com/us  
Revised: April 2026

